

Specialty Materials™

THE BEST GARMENT DECORATION PRODUCTS



LOVE what you PRESS!



Digital Decoration Systems®

ColorPrint™ Solvent/Ecosol

The best quality, brightest digital prints on the market! Maintains rebound through numerous washes and has excellent stretch and durability!



White CPS-2160

A white gloss polyurethane material with a semi-gloss to full gloss finish. Contains blockers to prevent dye migration (bleeding) from polyester and poly-blend fabrics and now has a thicker liner to reduce any curling issues. Designed for printing with solvent/eco-solvent printers and also compatible with latex printers.

We recommend using our DTM-855 Clear Transfer Mask.

If using latex ink, you must use our TM-854 Clear Transfer Mask, print uni-directional, and never heat above 100°C on the printer settings.

Please make sure this material is free of dust and debris before printing by wiping the material with a dry cloth. Always store roll in a plastic bag, protected from dust.

Application Instructions

Pre-Shrunk Cotton & Cotton/Blends, Uncoated Polyester, Spandex, Lycra, Wool, Linen

 45° Blade	 Print and cut this material "right-reading"	 Use DTM-855 Clear Transfer Mask to transfer image to the garment. Must use TM-854 for latex printers.	 PRESS Hard, even pressure
 275°F	 15 - 25 seconds	 PEEL Peel warm, almost hot	 Follow wash instructions for nylon. Turn inside out, cold water, tumble dry low.

Test on nylon, dazzle cloth, and shiny polyester. Follow wash instructions for nylon garments.

*** Instructions for application to moisture-wicking fabrics:**

Damp a cloth with rubbing alcohol (isopropyl alcohol), then gently apply it to the area on the garment you want to apply your design. Allow it to dry and apply your material. This will allow the adhesive to better penetrate the garment.

CAUTION: If using 100% Cotton OR Cotton/Blends, please be advised that if the fabric shrinks the design will wrinkle.



LOVE what you PRESS!

BASIC INSTRUCTIONS FOR PRINTING PROFILE SETUP

The following settings are to be used when no profile is available. Most self-adhesive gloss vinyl profiles work well with our printable media after a slight lowering of the ink limits.

To avoid over-saturation, it is important to remember to slow the printing process by using high resolution and high pass count settings to allow the ink to absorb without beading or bleeding.

When cutting printable media, it is important to use a new or sharp blade and slow the speed of the contour to 10cm/sec or less. Always perform test cuts to ensure proper depth before sending the final job.

Mimaki JV3 (SS2 Inks)

Profile: Use Gloss Vinyl Profile
Resolution: 720 x 1440 or 1440 x 1440
Pass count: 16 or 32
Direction: Uni
Heat: Pre- 35 deg C (95 deg F)
Print- 30 deg C (86 deg F)
Vacuum: High
GCR Option: Medium
Total Ink Limit: 220%
Black Ink Start: 0%
Black Ink Limit: 85%
Multi Ink Limits: M+Y = 82%
C +Y = 80%
C +M = 80%
C+Y+ M= 78%

Roland VersaCamm (Eco Max)

Profile: Use Gloss Vinyl Profile or
TTRH with Color Management
set to max impact
Print Quality: High Quality
Resolution: 1440 x 720dpi
Mode: CMYK(v) W+PASS
Halftone: Dither
Interpolation: Nearest Neighbor
Direction: Uni-direction
Pass Count: 18
Scan Speed: 750
Heat: Print - 95°F, Dryer - OFF
Vacuum: Strong
GCR Option: Medium
Total Ink Limit: 190%
Black Ink Start: 0%
Black Ink Limit: 75%
Multi Ink Limits: M+Y = 85%
C +Y = 78%
C +M = 93%
C+Y+ M= 85%

Technical Support: Toll Free: 877-437-8556 | SpecialtyMaterials.com

All technical information and recommendations are based on tests we believe to be reliable. However, we cannot guarantee performance for conditions not under manufacturer's control. Before using, please determine the suitability of product for its intended use. The user assumes all risk and liability whatsoever in connection with the use of this product. Seller's and manufacturer's only obligation shall be to replace such quantity of the product proved to be defective by manufacturer.