

# Specialty Materials™



THE BEST GARMENT DECORATION PRODUCTS

# LOVE what you PRESS!



## Digital Decoration Systems®

## ColorPrint™

### Nylon CPN-2150

Designed for thermal transfer printing and computer plotter-cutting.  
Special adhesive for nylon garments.

### Application Instructions

Nylon and other heat sensitive fabrics.



45° Blade



Print and cut  
this material  
"right-reading"



Use T&S Tape to remove  
image from paper backing  
and transfer the image to  
the garment.



300°F - 315°F



Hard,  
even  
pressure



30 seconds



PEEL

Peel cold. **Do not press  
twice - it will lose the  
gloss effect.**



Wash inside out,  
cold water, tumble  
dry low.

**Test on dazzle cloth, shiny polyester, and moisture-wicking materials.**

**Our ColorPrint materials were  
originally designed for thermal  
transfer printers. They work well on  
all other solvent/ecosol printers.**

These materials are also available 15" punched  
for Gerber brand printers

**Ask about wide format rolls!**



**These materials, when printed with solvent/eco-solvent inks,  
require 24 hour curing after printing, before pressing.**

Technical Support: Toll Free: 877-437-8556 | [SpecialtyMaterials.com](http://SpecialtyMaterials.com)

All technical information and recommendations are based on tests we believe to be reliable. However, we cannot guarantee performance for conditions not under manufacturer's control. Before using, please determine the suitability of product for its intended use. The user assumes all risk and liability whatsoever in connection with the use of this product. Seller's and manufacturer's only obligation shall be to replace such quantity of the product proved to be defective by manufacturer.

Copyright © 2014, Specialty Materials & Digital Decoration, LLC. All rights reserved. 2929 W. 21st Street, Tulsa, OK 74107