

Specialty Materials™



THE BEST GARMENT DECORATION PRODUCTS

LOVE what you PRESS!



Polybag Flex®

- CPSIA Certified
- Durable and weeds easily
- Pressure-sensitive carrier enables easy weeding and repositioning
- Apply at an even lower temperature



White

PPBF-0100



Black

PPBF-0236



Red

PPBF-0301

Applications

Polypropylene bags and other heat sensitive materials



45° Blade



Cut this material in mirror image



285°F



Medium to firm, even pressure



5 seconds



Peel warm or cold, cover with Teflon Sheet & repress for 10 seconds

No nylon, dazzle cloth, or shiny polyester. Be advised that dye migration has occurred with low energy dyes in polyester and poly-blend fabrics.

* Instructions for application to moisture-wicking materials:

Damp a cloth with rubbing alcohol (isopropyl alcohol), then rub it into the area on the garment you want to apply your design. Allow it to dry and apply your material. This will allow better adhesion to the garment.

* Instructions for application to dazzle cloth & shiny polyester fabrics:

We highly recommend that you TEST prior to doing large runs. Coated polyester can routinely cause adhesion issues.

Technical Support: Toll Free: 877-437-8556 | SpecialtyMaterials.com

All technical information and recommendations are based on tests we believe to be reliable. However, we cannot guarantee performance for conditions not under manufacturer's control. Before using, please determine the suitability of product for its intended use. The user assumes all risk and liability whatsoever in connection with the use of this product. Seller's and manufacturer's only obligation shall be to replace such quantity of the product proved to be defective by manufacturer.

Copyright © 2012, Specialty Materials & Digital Decoration, LLC. All rights reserved. 2929 W. 21st Street, Tulsa, OK 74107