

REFLECTION DECORATION™

RMSK & 200 Series

NEW 300 Series

-  **Magenta**
RMSK-506
-  **Mustard Yellow**
RMSK-2003
-  **Green**
RMSK-2004
-  **Black**
RMSK-2005
-  **Chameleon Reflective Black**
RMSK-12005H
-  **Dark Green**
RD-204
-  **Cobalt Blue**
RD-208
-  **Reflective Frosty Clear**
RD-2020
-  **Silver**
RD-300
-  **Tomato Red**
RD-301
-  **Royal Blue**
RD-302
-  **Dark Yellow**
RD-303
-  **Green**
RD-304
-  **Black**
RD-305
-  **White**
RD-306
-  **Gold**
RD-307
-  **Grey**
RD-309
-  **Neon Yellow**
RD-310
-  **Neon Red**
RD-311
-  **Neon Green**
RD-312
-  **Neon Orange**
RD-313
-  **Neon Pink**
RD-314
-  **Dark Grey**
RD-324
-  **Orange**
RD-325
-  **Violet**
RD-326
-  **Lemon Yellow**
RD-327
-  **Light Blue**
RD-328

- Use for nighttime visibility and brilliance in the spotlight
- Consists of very small glass beads that are embedded in a layer of polyester film
- The RD 200 series has a slightly sticky carrier for ease of weeding fine detail
- RMSK series: no sticky carrier; new RD 300 series: has sticky carrier and very easy to weed

Acceptable Fabrics

Cotton, Uncoated Polyester, Fabric Blends, Lycra, Wool, Linen **Excluding Nylon**

Thickness

RD Series: 8 mils/200 microns
Chameleon Black: 7.2 mils/180 microns
NEW RD (300 series): 7.5 mils/190 microns


Sizing Available

Available Widths (in.): 19" only, Chameleon Reflective Black 17.5" only
Available Lengths (ft.): 15', 30', 45', 60', 75', 90', & 162' rolls


Special Precautions

Will NOT stretch. Please note: The darker the color, the lower the reflectivity. Do not cut design and let it sit for more than 3 hours - it will separate from the carrier (excluding 300 series & Chameleon).


300 Series & Chameleon Reflective Black: NO PROTECTIVE LINER TO REMOVE




60° Blade




Cut this material in mirror image




300°F




Firm, even pressure



8 Seconds



HOT!
(Wait 2-3 seconds then peel)



Wash inside-out. Warm water, normal cycle. Tumble dry low heat. Not suitable for dry-cleaning or steam cleaning. No bleach. Do not iron directly onto the reflective vinyl.

Easily remove the heat liner with a piece of tape!



RMSK & 200 Series: REMOVE HEAT LINER BEFORE PLOTTING



60° Blade with slow cutting speed



Cut this material in mirror image



320°F



Firm, even pressure



Pre-press garment for 5 seconds, then press design for 3-5 seconds



Carefully peel warm, cover with Teflon and repress for 10-15 seconds at 320°F, let cool then remove Teflon.



Wash inside out. Warm water, gentle cycle. Tumble dry low heat. Suitable for dry-cleaning.

SpecialtyMaterials.com | 877.437.8556



Test on dazzle cloth and other moisture-wicking polyesters. Moisture-wicking materials have better adhesion when washed and dried using no fabric softener or blotted with rubbing alcohol before pressing. Be advised that dye migration has occurred with low energy dyes in polyester and poly-blend fabrics. All technical information and recommendations are based on tests we believe to be reliable. However, we cannot guarantee performance for conditions not under manufacturer's control. Before using, please determine the suitability of product for its intended use. The user assumes all risk and liability, whatsoever, in connection with the use of this product. Seller's and manufacturer's only obligation shall be to replace such quantity of the product proved to be defective by manufacturer.

Copyright © 2020, Specialty Materials & Digital Decoration, LLC. All rights reserved. Tulsa, OK 74107 | 866-437-8599