

Specialty Materials™

THE BEST GARMENT DECORATION PRODUCTS



DecoFILM® Paint FX

- Pearlescent transfer films that resemble the shimmer of new car paint
- Easy to cut and weed
- Can be used on sport and leisure wear
- Pressure-sensitive carrier enables easy weeding and repositioning

Acceptable Fabrics

Cotton, Uncoated Polyester, Fabric Blends, Spandex, Lycra, Wool, Linen
Excluding Nylon

Sizing Available

Available Widths (in.): 15" & 20"
Available Lengths (ft.): 15', 30', 45', 60', 75', and 90' rolls

Thickness

4 mils/100 microns



Pearl White
DFPX-5483



Champagne
DFPX-5484



Pink
DFPX-5485



Purple
DFPX-5486



Watermelon
DFPX-5487



Lime Yellow
DFPX-5488



Cobalt Blue
DFPX-5489



45° Blade
Recommended



Cut this material
in mirror image



310°F - 330°F



Firm, even
pressure



17-20 Seconds



Peel warm, cover
with Teflon Sheet
and re-press for
2 seconds



Wash inside out,
cold water, gentle
cycle. Dry low heat.
Suitable for dry-cleaning.



Technical Support: Toll Free: 877-437-8556 | SpecialtyMaterials.com

All technical information and recommendations are based on tests we believe to be reliable. However, we cannot guarantee performance for conditions not under manufacturer's control. Before using, please determine the suitability of product for its intended use. The user assumes all risk and liability whatsoever in connection with the use of this product. Seller's and manufacturer's only obligation shall be to replace such quantity of the product proved to be defective by manufacturer. Test on dazzle cloth and other moisture-wicking polyesters. Moisture-wicking materials have better adhesion when washed and dried using no fabric softener or blotted with rubbing alcohol before pressing. Be advised that dye migration has occurred with low energy dyes in polyester and poly-blend fabrics.

Copyright © 2019, Specialty Materials & Digital Decoration, LLC. All rights reserved.