



# Flocking Sheets

For use with our Hotmelt

Available in 20" x 14" sheets only (Packs of 5 per color)

- Add a 3D Flock effect to HotMelt or Screen Print adhesive
- Fuzzy high quality viscose Flock for a velvety feel
- Using with Hotmelt makes more detailed designs possible



### Application Instructions

Cotton, Uncoated Polyester, Cotton/Polyester, Polyester/Acrylic

#### Hotmelt



No longer has a liner



45° Blade with very low pressure



Cut this material in mirror image with the smooth side down.



300°F



Medium, even pressure



5 seconds



PEEL Peel warm, almost hot

#### Flock



Place Flocking sheet over the Hotmelt, cover with Teflon Sheet & press for 10 seconds. Rub with a cloth, let cool completely, then peel.



Wash inside out, gentle cycle, cold water, line dry. Not suitable for dry-cleaning.

#### No nylon.

##### \* Instructions for application to moisture-wicking materials:

Damp a cloth with rubbing alcohol (isopropyl alcohol), then rub it into the area on the garment you want to apply your design. Allow it to dry and apply your material. This will allow better adhesion to the garment.

##### \* Instructions for application to dazzle cloth & shiny polyester fabrics:

We highly recommend that you TEST prior to doing large runs. Coated polyester can routinely cause adhesion issues.

Technical Support: Toll Free: 877-437-8556 | [SpecialtyMaterials.com](https://SpecialtyMaterials.com)

All technical information and recommendations are based on tests we believe to be reliable. However, we cannot guarantee performance for conditions not under manufacturer's control. Before using, please determine the suitability of product for its intended use. The user assumes all risk and liability whatsoever in connection with the use of this product. Seller's and manufacturer's only obligation shall be to replace such quantity of the product proved to be defective by manufacturer.