SUBLIBLOCK®

- Sublimation resistant, even when exposed to high temperatures
- Soft hand with a matter finish
- Contains an additional layer that blocks dye-migration
- Pressure-sensitive carrier enables easy weeding and repositioning



Acceptable Fabrics

Cotton, Uncoated Polyester, Fabric Blends, Spandex, Lycra, Wool, Linen Excluding Nylon

Sizing Available

Available Widths (in.): 15" and 20" Available Lengths (ft.): 15', 30', 45', 60', and 90' rolls Thickness 5.2 mils/130 microns

Special Precautions

Do not pre-heat the garment.



45° Blade Recommended

Cut this material in mirror image

320°F - 330°F

Firm to hard, even pressure



10-15 Seconds



Peel Warm



Wash warm, tumble dry normal. Suitable for dry-cleaning.





SpecialtyMaterials.com | 877.437.8556 Materials

Test on dazzle cloth and other moisture-wicking polyesters. Moisture-wicking materials have better adhesion when washed and dried using no fabric softener or blotted with rubbing alcohol before pressing. Be advised that dye migration has occurred with low energy dyes in polyester and poly-blend fabrics. All technical information and recommendations are based on tests we believe to be reliable. However, we cannot guarantee performance for conditions not under manufacturer's control. Before using, please determine the suitability of product for its intended use. The user assumes all risk and liability, whatsoever, in connection with the use of this product. Seller's and manufacturer's only obligation shall be to replace such quantity of the product proved to be defective by manufacturer.

Copyright © 2022, Specialty Materials & Digital Decoration, LLC. All rights reserved. Tulsa, OK 74107 | 866-437-8599