



DecoFILM® Supers



FABRICS

Cotton, Uncoated Polyester, Fabric Blends, Spandex, Wool, and Linen - Excluding Nylon

SIZING

Available Widths (in.): 19.5" only
Available Lengths (ft.): 15', 30', and 81' rolls

THICKNESS

2.4 mils/60 microns

The Super styles offer a slightly softer hand and stretchability. Super Silver and Super Gold are Oeko-Tex Class II Certified. Manufactured without a pressure-sensitive carrier for easy stacking.



SPECIAL PRECAUTIONS

Warning: To avoid color fading after washing, you must press the material with silicone paper for an additional 3 seconds; if not, the washing resistance is considerably reduced; therefore, any claims regarding color fading WILL NOT be acknowledged in the future.



Super Silver
SS-5200



Super Gold
SG-5250

MIRRORING

Cut this material into a mirror image.



TEMPERATURE

310°F-315°F



CUTTING

45° Blade Recommended

PEELING

Peel cold



PRESSING | TIMING

Firm pressure | 10-15 seconds

LASER COMPATIBLE

This product contains no PVC and will not emit hazardous fumes.



WASHING

Wash inside out, gentle cycle, cold water, tumble dry low. Suitable for dry-cleaning.

"It's best to test!" Pre-test on an inconspicuous area before applying final production. Some garments require pre-heating and treatment, such as blotting moisture-wicking material with rubbing alcohol, before pressing the material. Dye migration may occur with low-energy dyes in polyester and blend fabrics. Check for compatibility and pre-treatment suggestions with each product's instructions. The user assumes all risk and liability whatsoever in connection with the use of this product. Specialty Materials cannot guarantee performance for conditions not under the manufacturer's control and is not responsible for issues due to third-party material qualities. The Seller's and manufacturer's only obligation shall be to replace such quantity of the product proved to be defective by the manufacturer.

©2025 Specialty Materials & Digital Decoration, LLC. | A POLI-TAPE Company | All rights reserved | Tulsa, OK 74146 | 877-437-8556

Tech Help: tech@specialtymaterials.com | Sample Request: samples@specialtymaterials.com