



# FROSTY CLEAR™



## FABRICS

Cotton, Uncoated Polyester, Cotton/Polyester, Polyester/Acrylic - Excluding Nylon


## SIZING

Available Widths (in.): 12", 15", 20", and 30"  
Available Lengths (ft.): 15', 30', 45', 60', 90', and 150' rolls  
Sheets: 12" x 15" | Pack of 20

## THICKNESS

3 mils/75 microns

Thin and transparent, UV-resistant, polyurethane film with a semi-matte finish. On dark fabrics, this adds a fashionable tone on tone look. \*PLS-9000 is manufactured without the pressure-sensitive carrier for easy stacking. PLS-9001 has a sticky carrier.



FROSTY CLEAR™  
\*PLS-9000  
PLS-9001



### TECH TIPS

You may layer designs with other products.

### MIRRORING

Cut this material into a mirror image.



### CUTTING

45° Blade Recommended



### TEMPERATURE

320°F-330°F



### PRESSING | TIMING

Medium pressure | 15 seconds



### PEELING

Peel cold, then cover with a PTFE sheet and re-press for 5 seconds.



### WASHING

Wash warm and tumble dry normal. Suitable for dry-cleaning.



### LASER COMPATIBLE

This product contains no PVC and will not emit hazardous fumes.



"It's best to test!" Pre-test on an inconspicuous area before applying final production. Some garments require pre-heating and treatment, such as blotting moisture-wicking material with rubbing alcohol, before pressing the material. Dye migration may occur with low-energy dyes in polyester and blend fabrics. Check for compatibility and pre-treatment suggestions with each product's instructions. The user assumes all risk and liability whatsoever in connection with the use of this product. Specialty Materials cannot guarantee performance for conditions not under the manufacturer's control and is not responsible for issues due to third-party material qualities. The Seller's and manufacturer's only obligation shall be to replace such quantity of the product proved to be defective by the manufacturer.

©2025 Specialty Materials & Digital Decoration, LLC. | A POLI-TAPE Company | All rights reserved | 12322 E 55th St, Tulsa, OK 74146 | 877-437-8556  
Tech Help: [tech@specialtymaterials.com](mailto:tech@specialtymaterials.com) | Sample Request: [samples@specialtymaterials.com](mailto:samples@specialtymaterials.com)