

ThermoFlex®STRETCH



FABRICS

Cotton, Uncoated Polyester, Fabric Blends, Spandex, Wool, Linen -**Excluding Nylon**

SIZING

Available Widths (in.): 15" and 20" Available Lengths (ff.): 15', 30', and 90' rolls

THICKNESS

4.2 mils/105 microns

Capacity for high stretch and rebound. Has a soft hand and strong grip. Durable and weeds easily. Pressure-sensitive carrier enables easy weeding and repositioning.



SPECIAL PRECAUTIONS

This product cannot be layered.



COLOR VARIATION


During manufacturing, color variation can occur between rolls. This is especially true for Neon colors.



TECH TIPS

For best results, perform test cuts.





Cut this material into a mirror image.

TEMPERATURE

45° Blade

320°F-330°F

ESSING | TIMING

Medium pressure | 15 seconds

Peel warm

PEEL

Wash warm and tumble dry normal. Suitable for dry-cleaning.

LASER COMPATIBLE
This product contains no PVC and will not emit hazardous fumes.

"It's best to test!" Pre-test on an inconspicuous area before applying final production. Some garments require pre-heating and treatment, such as blotting moisture-wicking material with rubbing alcohol, before pressing the material. Dye migration may occur with low-energy dyes in polyester and blend fabrics. Check for compatibility and pre-treatment suggestions with each product's instructions. The user assumes all risk and liability whatsoever in connection with the use of this product. Specialty Materials cannot guarantee performance for conditions not under the manufacturer's control and is not responsible for issues due to third-party material qualities. The Seller's and manufacturer's only obligation shall be to replace such quantity of the product proved to be defective by the manufacturer. ©2025 Specialty Materials & Digital Decoration, LLC. | A POLITAPE Company | All rights reserved | Tulsa, OK 74146 | 877-437-8556 Tech Help: tech@specialtymaterials.com | Sample Request: samples@specialtymaterials.com